

# SAFETY DATA SHEET

## \*\*\*\*\* SECTION I – IDENTIFICATION \*\*\*\*\*

**MANUFACTURER NAME**

Mullen Circle Brand, Inc.  
3514 West Touhy Avenue  
Skokie, Illinois 60076

**PHONE NUMBER**

847/676-1880

**EMERGENCY CONTACT**

800/535-5053

**PRODUCT NAME**

Adams Elevator  
Silicone Spray  
Part# APA140CC-CASE

**RECOMMENDED USE**

Lubricant

**E-Mail**

SDS@MullenOil.com

**RESTRICTIONS ON USE**

It is against federal law to use this product inconsistent with its labeling

## \*\*\*\*\* SECTION II – HAZARD(S) IDENTIFICATION \*\*\*\*\*

**OSHA Status**

Hazardous

**GHS HAZARD CLASS****Physical Hazards**

Flammable Aerosols – Category 1

**Health Hazards**

Serious eye damage/eye irritation – Category 2A  
Reproductive toxicity – Category 2  
Specific target organ toxicity, single exposure – Category 3 (Narcotic effects)  
Aspiration hazard – Category 1

**Environmental Hazards**

Hazardous to the aquatic environment, acute – Category 2  
Hazardous to the aquatic environment, chronic – Category 2

**GHS Symbol/Pictogram****Signal Word**

Danger

**Hazard Statements**

Extremely flammable aerosol  
Causes serious eye irritation  
Suspected of damaging fertility or the unborn child  
May cause drowsiness or dizziness  
May be fatal if swallowed & enters airways  
Toxic to aquatic life with long lasting effects  
Toxic to aquatic life

**PRODUCT NAME** Mullen Circle Brand, Inc.  
Adams Elevator Silicone Spray  
Part# APA140CC-CASE

**\*\*\*\*\* SECTION II – HAZARD(S) IDENTIFICATION (Continued) \*\*\*\*\***

**Precautionary Statements**

<b>Prevention</b>	<p>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not eat, drink or smoke when using this product Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Do not spray on an open flame or other ignition source Pressurized container, do not pierce or burn, even after use Take precautionary measures against static discharge Avoid breathing dust, fumes, gas, mist, vapors, spray Wash thoroughly after handling Use only outdoors or in a well ventilated area Wear protective gloves, protective clothing, eye protection, face protection Obtain special instructions before use. Do not handle until all safety precautions Have been read and understood</p>
<b>Response</b>	<p>IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician Do not induce vomiting IF ON SKIN: Wash with plenty of water IF ON SKIN (or hair): Remove contaminated clothing. Rinse skin with water If skin irritation occurs, get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention IF INHALED: Remove person to fresh air and keep comfortable for breathing Call a POISON CENTER/doctor/physician if you feel unwell Avoid contact during pregnancy and while nursing Specific treatment (see first aid section) In case of fire: Use foam, CO2, dry chemical</p>
<b>Storage</b>	<p>Store in a well ventilated place. Keep container closed when not in use Keep cool. Do not expose to temperatures above 122 F. Store locked up</p>
<b>Disposal</b>	<p>Dispose of contents/container in accordance with local/state/federal regulations Avoid release to the environment</p>

**\*\*\*\*\* SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS \*\*\*\*\***

**Substance** \_\_\_\_\_ **Mixture**   X  

Chemical Name	CAS#	%
Acetone	67-64-1	20-40
Butane	106-97-8	20-40
Propane	74-98-6	20-40
Aliphatic Petroleum Solvent	64742-89-8	2.5-10
Distillates (Petroleum), Hydrotreated Light	64742-47-8	2.5-10
n-Heptane	142-82-5	2.5-10
Polydimethylsiloxane	63148-62-9	2.5-10
Cyclohexane	110-82-7	1-2.5
n-Hexane	110-54-3	0.1-1
Toluene	108-88-3	0.1-1

**PRODUCT NAME** Mullen Circle Brand, Inc.  
Adams Elevator Silicone Spray  
Part# APA140CC-CASE

\*\*\*\*\* SECTION IV – FIRST AID MEASURES \*\*\*\*\*

**Description Of Necessary First Aid Measures**

**Eye Contact**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention.

**Skin Contact**

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Ingestion**

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

\*\*\*\*\* SECTION V – FIREFIGHTING MEASURES \*\*\*\*\*

**Extinguishing Media**

**Suitable**

Foam, CO2, dry chemicals, water fog or mist.

**Unsuitable**

Do not use water jet.

**Specific Hazards**

Flammable liquid and vapor. Contents under pressure. Pressurized container may explode when exposed to heat or flame. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

**Hazardous Decomposition Products**

Oxides of carbon, sulfur.

**Special Precautions – Fire Fighters**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if it can be done without risk. No action shall be taken involving any personal risk or without suitable training.

**Special Protective Equipment – Fire Fighters**

Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

**PRODUCT NAME** Mullen Circle Brand, Inc.  
Adams Elevator Silicone Spray  
Part# APA140CC-CASE

**\*\*\*\*\* SECTION VI – ACCIDENTAL RELEASE MEASURES \*\*\*\*\***

**Personal Precautions, Protective Equipment And Emergency Procedures**

**For Non-Emergency Personnel**

Take no action involving personal risk without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery, use care to avoid falling.

**For Emergency Responders**

If specialized clothing is required to deal with the spillage, take note of any information in Section VIII on suitable and unsuitable materials. See also the information in “For Non-Emergency Personnel”.

**Environmental Precautions**

Avoid dispersal of spilled products and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product causes environmental pollution.

**Methods And Materials For Containment And Cleaning Up**

**Small Spill**

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large Spill**

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

**\*\*\*\*\* SECTION VII – HANDLING & STORAGE \*\*\*\*\***

**Precautions For Safe Handling**

**Protective Measures**

Put on appropriate personal protective equipment (See Section VIII). Do not swallow. Avoid contact with eyes, skin, clothing. Avoid breathing vapor and mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Always bond receiving containers to the fill pipe before and during loading. Always confirm receiving container is properly grounded.

**Advice On General Occupational Hygiene**

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section VIII for additional information on hygiene measures.

**PRODUCT NAME** Mullen Circle Brand, Inc.  
 Adams Elevator Silicone Spray  
 Part# APA140CC-CASE

**\*\*\*\*\* SECTION VII – HANDLING & STORAGE (Continued) \*\*\*\*\***

**Conditions For Safe Storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section X) and food and drink. Keep away from heat, sparks and open flame. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**\*\*\*\*\* SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION \*\*\*\*\***

**Exposure Limits**

<b>Ingredient Name</b>	<b>Exposure Limits</b>	
Acetone	OSHA PEL-TWA	1000 ppm; 2400 mg/cubic meter
	ACGIH TLV-STEL	750 ppm; 1782 mg/cubic meter
	ACGIH TLV-TWA	500 ppm; 1188 mg/cubic meter
	NIOSH REL-TWA	250 ppm; 590 mg/cubic meter
Propane	OSHA PEL-TWA	1000 ppm; 1800 mg/cubic meter
	NIOSH REL-TWA	1000 ppm; 1800 mg/cubic meter
Butane	NIOSH REL-TWA	800 ppm; 1900 mg/cubic meter
	ACGIH TLV-STEL	1000 ppm
Aliphatic Petroleum Solvent	ACGIH TLV-TWA	400 ppm
n-Heptane	OSHA PEL-TWA	500 ppm; 2000 mg/cubic meter
	ACGIH TLV-STEL	500 ppm
	ACGIH TLV-TWA	400 ppm
	NIOSH REL-Ceiling	440 ppm; 1800 mg/cubic meter
	NIOSH REL TWA	85 ppm; 350 mg/cubic meter
Cyclohexane	OSHA PEL-TWA	300 ppm; 1050 mg/cubic meter
	ACGIH TLV-TWA	100 ppm
	NIOSH TLV-TWA	300 ppm; 1050 mg/cubic meter
n-Hexane	OSHA PEL-TWA	500 ppm; 1800 mg/cubic meter
	ACGIH TLV-TWA	50 ppm
	NIOSH REL-TWA	50 ppm; 180 mg/cubic meter
	Can be absorbed through the skin	
Toluene	OSHA PEL-Ceiling	300 ppm
	OSHA PEL-TWA	200 ppm
	ACGIH TLV-TWA	20 ppm
	NIOSH REL-STEL	150 ppm; 560 mg/cubic meter
	NIOSH REL-TWA	100 ppm; 375 mg/cubic meter
	Can be absorbed through the skin	

**PRODUCT NAME** Mullen Circle Brand, Inc.  
Adams Elevator Silicone Spray  
Part# APA140CC-CASE

\*\*\*\*\* SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION (continued) \*\*\*\*\*

**Environmental Exposure Controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Appropriate Engineering Controls**

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

**Hygiene Measures**

Wash hands, forearms and face thoroughly after handling chemical products and before eating, smoking or using the lavatory as well as at the end of the work period. Wash contaminated clothing before reusing.

**Respiratory Protection**

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits.

**Eye Protection**

Safety glasses equipped with side shields in conjunction with a face shield are recommended in industrial settings.

**Skin Protection**

Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

\*\*\*\*\* SECTION IX – PHYSICAL & CHEMICAL PROPERTIES \*\*\*\*\*

**Appearance**

<b>Form</b>	Aerosol
<b>Physical State</b>	Gas
<b>Color</b>	Clear

<b>Odor</b>	Mild solvent
<b>Odor Threshold</b>	Not available

<b>Ph</b>	None
<b>Melting Point</b>	Not available
<b>Freezing Point</b>	Not available
<b>(Pour Point)</b>	

<b>Drop Point</b>	Not applicable
<b>Flash Point</b>	-156.00 F Propellant

<b>Evaporation Rate</b>	Faster than water
-------------------------	-------------------

<b>Vapor Pressure</b>	50-70 psig @ 70 F estimated
<b>Vapor Density</b>	Not available

<b>Specific Gravity</b>	.772
<b>Solubility</b>	Insoluble in water

**PRODUCT NAME** Mullen Circle Brand, Inc.  
Adams Elevator Silicone Spray  
Part# APA140CC-CASE

**\*\*\*\*\* SECTION X – STABILITY & REACTIVITY**

**Reactivity**

Bulk product not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS definitions

**Chemical Stability**

This product is stable under normal conditions.

**Possibility Of Hazardous Reactions**

Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions To Avoid**

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

**Incompatible Materials**

Reactive or incompatible with the following materials: Oxidizing materials.

**Hazardous Decomposition Products**

Oxides of carbon and sulfur.

**\*\*\*\*\* SECTION XI – TOXICOLOGICAL INFORMATION \*\*\*\*\***

**Primary Routes Of Exposure:**

Eye contact, Ingestion, Inhalation, Skin contact

**Acute Toxicity Values:**

Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

**Information On Toxicological Effects - Effects Of Overexposure**

**Inhalation**

Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). Causes delayed lung injury.

**Skin Contact**

Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

**Eye Contact**

Contact with the eye causes serious irritation. May cause tearing, redness and discomfort.

**Ingestion**

Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

**Chronic Hazards**

Possible brain damage from overexposure. Overexposure may cause nervous system damage.

**PRODUCT NAME** Mullen Circle Brand, Inc.  
Adams Elevator Silicone Spray  
Part# APA140CC-CASE

\*\*\*\*\* **SECTION XI – TOXICOLOGICAL INFORMATION** \*\*\*\*\*

<b>Sensitization</b>	
<b>Respiratory</b>	Not classified
<b>Skin Sensitization</b>	Not classified
<b>Germ Cell Mutagenicity</b>	Non-mutagenic based on a Modified Ames Assay.
<b>Carcinogenicity</b>	Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346. This product is not listed as a carcinogen by IARC, OSHA, NTP.
<b>Fertility Effects</b>	Suspected of damaging fertility
<b>Specific Target Organ Toxicity</b>	
<b>Single Exposure</b>	Category 3 - Narcotic effects
<b>Repeated Exposure</b>	Not classified
<b>Aspiration Hazard</b>	May be fatal if swallowed and enters airways

\*\*\*\*\* **SECTION XII – ECOLOGICAL INFORMATION** \*\*\*\*\*

**Ecotoxicity**  
Toxic to aquatic life with long lasting effects

**Persistence & Degradability**  
Not available

**Bioaccumulative Potential**  
Not available

**Mobility In Soil**  
Not available

**Other Adverse Effects**  
No known significant effects or critical hazards.

\*\*\*\*\* **SECTION XIII – DISPOSAL CONSIDERATIONS** \*\*\*\*\*

**Disposal Methods**  
Waste generation should be avoided or minimized wherever possible. Dispose of in accordance with federal, state, and local regulations. After the container has been emptied, it may contain hazardous residues. Avoid sparks and open flame. Do not cut, puncture, or weld on or near the container. Do not reuse the container for any purpose until properly reconditioned.

**RCRA Classification**  
Hazardous Waste



**PRODUCT NAME** Mullen Circle Brand, Inc.  
Adams Elevator Silicone Spray  
Part# APA140CC-CASE

\*\*\*\*\* SECTION XIV – TRANSPORT INFORMATION \*\*\*\*\*

**DOT**

<b>UN#</b>	UN1950
<b>UN SHIPPING NAME</b>	Aerosols, flammable, (each not exceeding 1 L capacity)
<b>Transport Hazard class</b>	Class 2.1
<b>Packing Group</b>	Not Available

\*\*\*\*\* SECTION XV – REGULATORY INFORMATION \*\*\*\*\*

**TSCA Section 12(b) Export notification (40 CFR 707 Subpart D):** None

**CERCLA Hazardous Substance List (40 CFR 302.4):** Acetone  
Cyclohexane  
n-Hexane  
Toluene

**US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed

**SARA Section 302 – Threshold Planning Quantity :** None

**SARA Title III – Section 311/312**

<b>Immediate/Acute Health Effects</b>	: Yes
<b>Fire Hazard</b>	: Yes
<b>Delayed/Chronic Health Effects</b>	: Yes
<b>Reactivity Hazard</b>	: No
<b>Sudden Release Of Pressure Hazard</b>	: Yes

**Chemical Release Reporting:**

<b>SARA Section 313</b>	: Not listed
<b>CERCLA</b>	: Not listed

**TSCA Inventory** : All product ingredients are listed on the chemical inventory.

**Clean Air Act**

**Section 112 Hazardous Air Pollutants** : n-Hexane, Toluene

**Section 112(r) Accidental Release Prevention:** Butane, Propane

\*\*\*\*\* SECTION XVI – OTHER INFORMATION \*\*\*\*\*

The above mentioned information is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition the person receiving it shall make his own determination as to the suitability of the material for his particular use and on the condition he assume the risk of his use thereof.

Revision Date: August 1, 2016